

Pinion	Lautas pyörä	Välitys	Käyttö
7	17	2.429	
9	22	2.444	
11	27	2.455	
13	32	2.462	
15	37	2.467	
15	38	2.533	
13	33	2.538	
11	28	2.545	
9	23	2.556	
16	41	2.563	
7	18	2.571	
14	36	2.571	
12	31	2.583	
10	26	2.600	
15	39	2.600	
13	34	2.615	
8	21	2.625	
16	42	2.625	
11	29	2.636	
14	37	2.643	
9	24	2.667	
12	32	2.667	
15	40	2.667	
16	43	2.688	
13	35	2.692	
10	27	2.700	
7	19	2.714	
14	38	2.714	
11	30	2.727	
15	41	2.733	
8	22	2.750	
12	33	2.750	
16	44	2.750	
13	36	2.769	
9	25	2.778	
14	39	2.786	
10	28	2.800	
15	42	2.800	
16	45	2.813	
11	31	2.818	
12	34	2.833	RR, LR (KAM)
13	37	2.846	
7	20	2.857	
14	40	2.857	
15	43	2.867	
8	23	2.875	
16	46	2.875	
9	26	2.889	
10	29	2.900	
11	32	2.909	
12	35	2.917	
13	38	2.923	
14	41	2.929	
15	44	2.933	
16	47	2.938	
16	49	3.063	
15	46	3.067	
14	43	3.071	
13	40	3.077	
12	37	3.083	
11	34	3.091	
10	31	3.100	
9	28	3.111	
8	25	3.125	
16	50	3.125	

Pinion	Lautas pyörä	Välitys	Käyttö
15	76	5.067	
14	71	5.071	
13	66	5.077	
12	61	5.083	
11	56	5.091	
10	51	5.100	
9	46	5.111	
8	41	5.125	GAZ, UAZ vanhat
16	82	5.125	
15	77	5.133	
7	36	5.143	
14	72	5.143	
13	67	5.154	
12	62	5.167	
11	57	5.182	
16	83	5.188	
10	52	5.200	
15	78	5.200	
14	73	5.214	
9	47	5.222	
13	68	5.231	
8	42	5.250	
12	63	5.250	
16	84	5.250	
15	79	5.267	
11	58	5.273	
7	37	5.286	
14	74	5.286	
10	53	5.300	
13	69	5.308	
16	85	5.313	
9	48	5.333	
12	64	5.333	
15	80	5.333	
14	75	5.357	
11	59	5.364	
8	43	5.375	UAZ portaaliakseli
16	86	5.375	
13	70	5.385	
10	54	5.400	
15	81	5.400	
12	65	5.417	
7	38	5.429	
14	76	5.429	
16	87	5.438	
9	49	5.444	
11	60	5.455	
13	71	5.462	
15	82	5.467	
15	83	5.533	
13	72	5.538	
11	61	5.545	
9	50	5.556	
16	89	5.563	
7	39	5.571	
14	78	5.571	
12	67	5.583	
10	56	5.600	
15	84	5.600	
13	73	5.615	
8	45	5.625	
16	90	5.625	
11	62	5.636	
14	79	5.643	
9	51	5.667	

RR = Range Rover

LR = Land Rover

std = vakiovälitys

KAM = KAM Differentialsin erikoisvälitys

Pinion	Lautas pyörä	Välitys	Käyttö
15	47	3.133	
7	22	3.143	
14	44	3.143	
13	41	3.154	
12	38	3.167	
11	35	3.182	
16	51	3.188	
10	32	3.200	
15	48	3.200	
14	45	3.214	
9	29	3.222	
13	42	3.231	
8	26	3.250	
12	39	3.250	
16	52	3.250	
15	49	3.267	
11	36	3.273	
7	23	3.286	
14	46	3.286	
10	33	3.300	
13	43	3.308	
16	53	3.313	
9	30	3.333	
12	40	3.333	
15	50	3.333	
14	47	3.357	
11	37	3.364	
8	27	3.375	
16	54	3.375	
13	44	3.385	
10	34	3.400	
15	51	3.400	
12	41	3.417	
7	24	3.429	
14	48	3.429	
16	55	3.438	
9	31	3.444	Volvo 7.05:1-akseli
11	38	3.455	
13	45	3.462	
15	52	3.467	
8	28	3.500	
15	53	3.533	
13	46	3.538	RR, LR (std+KAM)
24	85	3.542	Range Rover uudet
11	39	3.545	
9	32	3.556	
16	57	3.563	
7	25	3.571	
14	50	3.571	
12	43	3.583	
10	36	3.600	
15	54	3.600	
13	47	3.615	
8	29	3.625	
16	58	3.625	
11	40	3.636	
14	51	3.643	
9	33	3.667	Volvo 7.55:1-akseli
12	44	3.667	
15	55	3.667	
16	59	3.688	
13	48	3.692	
10	37	3.700	
7	26	3.714	
14	52	3.714	

Pinion	Lautas pyörä	Välitys	Käyttö
12	68	5.667	
15	85	5.667	
16	91	5.688	
13	74	5.692	
10	57	5.700	
7	40	5.714	
14	80	5.714	
11	63	5.727	
15	86	5.733	
8	46	5.750	
12	69	5.750	
16	92	5.750	
13	75	5.769	
9	52	5.778	
14	81	5.786	
10	58	5.800	
15	87	5.800	
16	93	5.813	
11	64	5.818	
12	70	5.833	
13	76	5.846	
7	41	5.857	
14	82	5.857	
15	88	5.867	
8	47	5.875	
16	94	5.875	
9	53	5.889	
10	59	5.900	
11	65	5.909	
12	71	5.917	
13	77	5.923	
14	83	5.929	
15	89	5.933	
16	95	5.938	
16	97	6.063	
15	91	6.067	
14	85	6.071	
13	79	6.077	
12	73	6.083	
11	67	6.091	
10	61	6.100	
9	55	6.111	
8	49	6.125	
16	98	6.125	
15	92	6.133	
7	43	6.143	
14	86	6.143	
13	80	6.154	
12	74	6.167	
11	68	6.182	
16	99	6.188	
10	62	6.200	
15	93	6.200	
14	87	6.214	
9	56	6.222	
13	81	6.231	
8	50	6.250	
12	75	6.250	
16	100	6.250	
15	94	6.267	
11	69	6.273	
7	44	6.286	
14	88	6.286	
10	63	6.300	
13	82	6.308	

RR = Range Rover  
LR = Land Rover

std = vakiovälitys  
KAM = KAM Differentialsin erikoisvälitys

Pinion	Lautas pyörä	Välitys	Käyttö
11	41	3.727	
15	56	3.733	
8	30	3.750	
12	45	3.750	
16	60	3.750	
13	49	3.769	
9	34	3.778	
14	53	3.786	
10	38	3.800	RR, LR (KAM)
15	57	3.800	
16	61	3.813	
11	42	3.818	
12	46	3.833	
13	50	3.846	
7	27	3.857	
14	54	3.857	
15	58	3.867	
8	31	3.875	
16	62	3.875	
9	35	3.889	
10	39	3.900	Niva 95->, Toyota JTx07x...
11	43	3.909	
12	47	3.917	
13	51	3.923	
14	55	3.929	
15	59	3.933	
16	63	3.938	
16	65	4.063	
15	61	4.067	
14	57	4.071	
13	53	4.077	
12	49	4.083	
11	45	4.091	
10	41	4.100	RR, LR (KAM), Niva 84-92 (95), Toyota JTx29x...
9	37	4.111	
8	33	4.125	
16	66	4.125	
15	62	4.133	
7	29	4.143	
14	58	4.143	
13	54	4.154	
12	50	4.167	
11	46	4.182	
16	67	4.188	
10	42	4.200	RR, LR (KAM)
15	63	4.200	
14	59	4.214	
9	38	4.222	
13	55	4.231	
8	34	4.250	
12	51	4.250	
16	68	4.250	
15	64	4.267	
11	47	4.273	
7	30	4.286	
14	60	4.286	
10	43	4.300	Niva 78-84, Toyota JTx28x...
13	56	4.308	
16	69	4.313	
9	39	4.333	
12	52	4.333	
15	65	4.333	
14	61	4.357	
11	48	4.364	
8	35	4.375	Toyota JTx10x...

Pinion	Lautas pyörä	Välitys	Käyttö
16	101	6.313	
9	57	6.333	
12	76	6.333	
15	95	6.333	
14	89	6.357	
11	70	6.364	
8	51	6.375	
16	102	6.375	
13	83	6.385	
10	64	6.400	
15	96	6.400	
12	77	6.417	
7	45	6.429	
14	90	6.429	
16	103	6.438	
9	58	6.444	
11	71	6.455	
13	84	6.462	
15	97	6.467	
15	98	6.533	
13	85	6.538	
11	72	6.545	
9	59	6.556	
16	105	6.563	
7	46	6.571	
14	92	6.571	
12	79	6.583	
10	66	6.600	
15	99	6.600	
13	86	6.615	
8	53	6.625	
16	106	6.625	
11	73	6.636	
14	93	6.643	
9	60	6.667	
12	80	6.667	
15	100	6.667	
16	107	6.688	
13	87	6.692	
10	67	6.700	
7	47	6.714	
14	94	6.714	
11	74	6.727	
15	101	6.733	
8	54	6.750	
12	81	6.750	
16	108	6.750	
13	88	6.769	
9	61	6.778	
14	95	6.786	
10	68	6.800	
15	102	6.800	
16	109	6.813	
11	75	6.818	
12	82	6.833	
13	89	6.846	
7	48	6.857	
14	96	6.857	
15	103	6.867	
8	55	6.875	
16	110	6.875	
9	62	6.889	
10	69	6.900	
11	76	6.909	
12	83	6.917	

RR = Range Rover

std = vakiovälitys

LR = Land Rover

KAM = KAM Differentialsin erikoisvälitys

